

Product datasheet

Floor lamp, Iretta, anthracite, 220-240V AC/50-60Hz, 4,00 W, warmwhite

Technical Data

General Characteristics

Material	aluminum die casting
Colour	anthracite
Optics	
included in delivery	



Electrical Characteristics

Power / power consumption	4,00 W / 4,20 W
Input Voltage	220-240V AC/50-60Hz
Input current	
Base (standard designation)	
Number of Bases	
Power supply unit	incl. LED-power supply unit
Electronically reversible	not dimmable
Connection possibility	clamp
Protection class I, II, III	I

Light Technical Data

Bulb	LED-module fixed
Colour Designation	warmwhite
Colour temperature	3000 K
Luminous flux	240 lm
Beam angle	110°
LED type	SMD
LED quantity	48
Spectral power distribution	



Product datasheet

Floor lamp, Iretta, anthracite, 220-240V AC/50-60Hz, 4,00 W, warmwhite

Light Direction


Rotating and tilting range	fixed
Angle of inclination	
Radiation direction	
Reflector / lense	symmetrisch

Dimensions & Weight

Length	165 mm
Width	192 mm
Height	700 mm
Diameter	
Product Weight	1879 g

Absolute maximum ratings

The LED will get damaged and the lifetime will decrease when you overrun absolute maximum ratings.	
Working temperature	-20°C - +50°C
Storage temperature	-10°C - +60°C
IP - Code	IP44



Product datasheet

Floor lamp, Iretta, anthracite, 220-240V AC/50-60Hz, 4,00 W, warmwhite




General product data

Environmental Characteristics

Energy label	A
Energy consumption	5 kWh/1000h

Lifespan

Lamp life time	25000 h
Luminous flux (end of lifetime)	0,70
Number of switching cycles	100000

IP44	Protection against penetration of foreign objects > 1 mm. Protection against penetration of splashing water.
	Lightings of Protection Class I in which the protection against electric shock is not based solely on isolation, but an additional safety measure contains such a way that accessible conductive parts are equipped with means for connection to the protective conductor of the fixed installation, so that in case of failure of the basic insulation exposed conductive parts cannot be active.
	Because of the complex manufacturing process of the LED the above shown data are just a statistical size, which is not forced to be the realistic data of every LED.
	The light source of this luminaire may only be replaced by the manufacturer or by a service technician appointed by him or by a comparable qualified person