

Art. no. 730487

Damp-proof light Tri Proof Basic, Motion, 36 W, 4,000 K



Discover our TRI PROOF BASIC damp-proof light. The damp-proof lights are eligible for BEG German federal funding for energy-efficient buildings and are particularly energy efficient, which means lower operating costs for your customers. With durable construction and a long service life, the lights are very long-lasting. The pre-installed feed-through wiring and the practical cable entry points on the back significantly simplify installation. The metal clips ensure they are secured reliably. We also offer variants with a motion detector, where the brightness threshold, detection range and switch-off delay can be adjusted.

Special features

- Eligible for BEG German federal funding for energy-efficient buildings
- Particularly energy efficient
- Long service life of 50,000 hours L80B50
- Pre-installed feed-through wiring 3x1.5 mm²/5x1.5 mm² [DALI]
- Cable entry point on the back
- Stainless steel clips on the cover can be locked with screws
- Robust polycarbonate [PC] plastic housing
- Adjustable radar motion sensor [730484, 730487, 730490 only]

Housing Material	Polycarbonate (PC)/iron
Housing Color	Grey
Protection Class	Protection class I/protective grounding
Rated Input	36 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Number of Cable Entries	2
Cable Gland Diameter	12 mm
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	High frequency
Detection Distance	4-6 m
Angle of Detection	360 Degree
Light Source	LED, Light source changeable TC
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	5040 lm
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Length	1210 mm
Width	82 mm
Height	75 mm
Working Temperature	-20 to 40 °C
Storage Temperature	-40 to 75 °C
IP Protection Class	IP 65

IK Protection Class	IK08
Life Time L80 / B50	50000 h
Switching Cycles	25000
Power Consumption	36 kWh/1000h
Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class C.