

**Special features**

- Replaceable GU10 lamp (retrofit)
- Incl. 2 m connecting cable with IP44 plug
- Incl. ground spike
- Incl. cover (art. no. 732161 only)

Housing Material	Aluminium, Plastic	IK Protection Class	IK05
Housing Color	Grey		
Housing Surface	Matt		
Material of Lens	Glass		
Colour of Lens	Clear		
Protection Class	Protection class I/protective grounding		
max. Power	1x max. 35 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Socket Description	GU10		
Socket Quantity	1		
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Power plug		
Primary Cable Length	2 m		
Dimmable	Yes		
Control	Dimmable via optional light source		
Motion Detector	No		
Execution	Without lamp		
Swivel Angle	180 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		
Height	420 mm		
Diameter	60 mm		
Product weight	651 g		
Working Temperature	-10 to 45 °C		
Storage Temperature	-20 to 60 °C		
IP Protection Class Lamp	IP 65		
IP Protection Class Plug	IP 44		