



The ceiling lights from the LUCEA DTW series are available with an output of 10 W. They provide up to 750 lumens of light output. The light emission angle can be narrowed or expanded by changing the optionally available lenses. The dim-to-warm function changes the colour temperature as the lights dim.

#### Special features

- Dim-to-warm 1,800K-2,700K
- Incl. black reflector ring
- Comprehensive range of accessories for customisation

<b>Housing Material</b>	Aluminium	<b>Life Time L70 / B50</b>	50000 h
<b>Housing Color</b>	White	<b>Switching Cycles</b>	100000
<b>Material of Lens</b>	PMMA	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class F.
<b>Functions</b>	Dim to warm		
<b>Protection Class</b>	Protection class I/protective grounding		
<b>Rated Input</b>	10 W		
<b>Rated Power Consumption Standby</b>	0.5 W		
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Dimmable</b>	Yes		
<b>Control</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Colour Temperature</b>	1800-2700 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Luminous Flux</b>	750 lm		
<b>Rated Angle of Reflection</b>	36 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Height</b>	157 mm		
<b>Diameter</b>	65 mm		
<b>Working Temperature</b>	-20 to 40 °C		
<b>Storage Temperature</b>	-20 to 65 °C		
<b>IP Protection Class</b>	IP 20		