



The ceiling lights from the LUCEA DTW series are available with an output of 10 W. They provide up to 750 lumens of light output. The light emission angle can be narrowed or expanded by changing the optionally available lenses. The dim-to-warm function changes the colour temperature as the lights dim.

Special features

- Dim-to-warm 1,800K-2,700K
- Incl. black reflector ring
- Comprehensive range of accessories for customisation

Housing Material	Aluminium	Life Time L70 / B50	50000 h
Housing Color	Black	Switching Cycles	100000
Material of Lens	PMMA	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class F.
Functions	Dim to warm		
Protection Class	Protection class I/protective grounding		
Rated Input	10 W		
Rated Power Consumption Standby	0.5 W		
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Dimmable	Yes		
Control	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Colour Temperature	1800-2700 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	750 lm		
Rated Angle of Reflection	36 Degree		
Light Distribution	Symmetric		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	157 mm		
Diameter	65 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-20 to 65 °C		
IP Protection Class	IP 20		