



LUCEA series rotating and swivelling ceiling lights are available with 6, 10, 15, 20 and 30 W output. The lights can be customised with a rotation angle of 350° and a swivel angle of 90°. They provide up to 2,900 lumens of light output depending on the design. The light emission angle can be narrowed or expanded by exchanging optionally available lenses.

Special features

- incl. black reflector ring
- Can be customised with a wide range of accessories

Housing Material	Aluminium	Working Temperature	-20 to 40 °C
Housing Color	White	Storage Temperature	-20 to 65 °C
Material of Lens	PMMA	IP Protection Class	IP 20
Protection Class	Protection class I/protective grounding	Life Time L70 / B50	50000 h
Rated Input	10 W	Switching Cycles	100000
Rated Power Consumption Standby	1 W	Power Consumption	10 kWh/1000h
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	Yes		
Control	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	2700 K		
Colour Consistency	5 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	1300 lm		
Rated Angle of Reflection	36 Degree		
UGR	16		
Swivel Angle	90 Degree		
Rotation Angle	350 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	157 mm		
Diameter	65 mm		
Base height	29 mm		
Base diameter	103.5 mm		