


Special features

- Very low glare value
- Service life 50,000 h L80B10
- Dimmable using rotary switch
- Ready to use including 2.5 m connecting cable

Housing Material	Aluminium	Light direction	Top, Below
Housing Color	Silver		
Material of Lens	Acryl	Length	610 mm
Colour of Lens	White	Width	280 mm
Protection Class	Protection class I/protective grounding	Height	1950 mm
Rated Input	80 W	Product weight	14000 g
Rated Power Consumption	0.5 W	Working Temperature	-20 to 45 °C
Standby		Storage Temperature	-40 to 80 °C
Rated Input Voltage	200-240 V/AC 50 / 60 Hz	IP Protection Class	IP 20
Frequency			
Power Supply Unit incl.	No	Life Time L70 / B50	50000 h
Connection Cable Primary	Yes	Life Time L80 / B10	50000 h
Primary Connection	Power plug	Switching Cycles	25000
Primary Cable Length	2.5 m	Power Consumption	80 kWh/1000h
Connection Type According to Standard	Typ Y	EEI	E
Dimmable	Yes		
Control	Touch-Sensor		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Lightcolor	Neutral white		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	8300 lm		
Luminous Efficiency	103.8 lm/W		
Rated Angle of Reflection	110 Degree		
Rated Angle of Reflection 2	90 Degree		
UGR	19		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	2		
Light characteristics	Direct		

